

SurfMet® 1

Metallographic and Spectrographic
Belt Surfacers



BUEHLER

Excellent Results. Easily Repeatable.™

Buehler SurfMet® I Belt Surfacers make grinding metallographic or spectrographic samples easy and efficient. Features 1/3 horsepower (249W), heavy-duty, fused motors for superior durability and performance. Replaceable stainless steel wear plates are designed to maximize machine life. Separate belt flushing and coolant controls guarantee adequate removal of particulate matter from the grinding belt, for efficient cutting action, while providing critical specimen cooling. The stainless steel sink with faucet allows the convenience of quickly grinding and washing the specimen in one location; this feature is particularly useful between coarse and fine grinding steps and for production applications.

The SurfMet® I Belt Surfacers are offered as tabletop models mounted on sturdy TechMet® tables with chemical-resistant laminate tops. The optional recirculating system utilizes a corrosion inhibiting lubricant that extends machine life, provides faster, cleaner grinding, and collects swarf for environmentally correct disposal.

Specifications

16-1270-160 SurfMet® I Belt Surfacers, corrosion-resistant modified epoxy coated cabinet, 4 x 9" (10.2 x 22.9 cm) grinding area, cam operated device, belt coolant, and compartment flushing system, stainless steel sink with faucet, illuminated on-off switch, 115V/60Hz/1 phase, 1/3 Hp (249W) fused motor. Includes three CarbiMet® MetSplice Abrasive Belts and operating instructions. Dimensions: 18 W x 21 D x 11" H (46 x 53 x 28cm). Shipping weight: 95 lbs. (43kg).

16-270-250 SurfMet® I Belt Surfacers, same as 16-1270-160, but for operation on 220-240V/50Hz/1 phase.

Accessories

10-1250-160 Recirculating System, including baffled and compartmented tank, 115V/50-60Hz/1 phase, 1/15 Hp (50W) motor connected directly to pump. Dimensions: 13 W x 21 D x 16" H (33 x 53 x 41cm). Shipping weight: 75 lbs. (34kg).

10-1250-250 Recirculating System, same as 10-1250-160, but for operation on 220-240V/50Hz/1 phase.

16-1279 Copper Wear Plate Retrofit Kit, for Dry Grinding Applications.

16-1278 Wear Plate Replacement Kit, for Belt Surfacers.

16-3170 Hose and Connector Assembly, for connection of SurfMet® I tabletop model to Recirculating System.

For a complete listing of consumables, please refer to our Consumables Buyer's Guide. Buehler continuously makes product improvements; therefore, technical specifications are subject to change without notice.



BUEHLER



BUEHLER®, a division of Illinois Tool Works Inc.
– **Worldwide Headquarters**
41 Waukegan Road
Lake Bluff, Illinois 60044-1699 USA
Tel: (847) 295-6500 • Fax: (847) 295-7979
Sales: 1-800-BUEHLER (1-800-283-4537)
www.buehler.com
Email: info@buehler.com

BUEHLER GmbH - European and MESA Headquarters
In der Steele 2 • 40599 Düsseldorf
Telefon: (49) 211 974100 • Telefax: (49) 211 9741079
www.buehler-met.de
Email: info@buehler-met.de

BUEHLER FRANCE
Téléphone: 0800 89 73 71
Télécopie: 0800 88 05 27
www.buehler.fr
Email: info@buehler.fr

BUEHLER UNITED KINGDOM
Telephone: 0800 707 6273
Fax: 0800 707 6274
www.buehler.co.uk
Email: sales@buehler.co.uk

BUEHLER CANADA
10 Carlow Court, Unit #2
Whitby, Ontario L1N 9T7
Telephone: (905) 430-4684
Fax: (905) 430-4647
Sales Telephone: 1-800-268-3593
Email: info@buehler.ca

BUEHLER, ASIA-PACIFIC
5/F Vogue Centre
696 Castle Peak Road
Lai Chi Kok, Kowloon
Hong Kong, SAR, China
Telephone: (852) 2307 0909
Fax: (852) 2307 0233