

Issuing Date 15-Sep-2016

Revision Date 13-Apr-2017

Revision Number 3

Japan / English

1. PRODUCT AND COMPANY IDENTIFICATION**Product identifier**

Product Name Release Agent
Product Code(s) 20-8185-002, 20-8185-008, 20-8185-016, 20-8185-032, 20-8186-004, 20-8186-032
(M)SDS Number 1350448_J

Other means of identification

Synonyms No information available
Registration Number(s) No information available

Recommended use of the chemical and restrictions on use

Recommended Use Laboratory Use Only
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Buehler
Manufacturer Address Loop-X 6th Floor 3-9-15
kaigan Minato-ku, Tokoyo 108-0022
www.buehler.com/Japan
Phone number +81 (0)3 5439 5077
E-mail Address info.japan@buehler.com

Emergency telephone number

Global Access Code: 334545
Asia Pacific: +1 760 476 3960 Americas: +1 760 476 3962
Middle East/Africa: +1 760 476 3959 Europe: +1 760 476 3961
Japan: +81 36 8908677

2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids	Category 2
Aspiration toxicity	Category 1
Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Acute aquatic toxicity	Category 1

Chronic aquatic toxicity	Category 1
--------------------------	------------

Label elements



Signal word

Danger

Hazard statements

- H225 - Highly flammable liquid and vapor
- H304 - May be fatal if swallowed and enters airways
- H315 - Causes skin irritation
- H336 - May cause drowsiness or dizziness
- H410 - Very toxic to aquatic life with long lasting effects

Precautionary Statements - Prevention

- Wash face, hands and any exposed skin thoroughly after handling
- Do not breathe dust/fume/gas/mist/vapors/spray
- Do not eat, drink or smoke when using this product
- Avoid release to the environment
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- Keep container tightly closed
- Use explosion-proof electrical/ ventilating/ lighting/ equipment
- Ground/bond container and receiving equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

- Specific treatment (see supplemental first aid instructions on this label)
- IF EXPOSED OR CONCERNED: Call a POISON CENTER or doctor
- IF SKIN IRRITATION OCCURS: Get medical advice/attention
- IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/ shower
- Wash contaminated clothing before reuse
- IF SWALLOWED: Immediately call a POISON CENTER or doctor
- Do NOT induce vomiting
- In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
- Collect spillage

Precautionary Statements - Storage

- Store locked up
- Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

- Dispose of contents/container to an approved waste disposal plant

Other hazards

Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Chemical name	Weight-%	ENCS - Japan Existing and New Chemical Substances	ISHL No.	CAS No
Isooctane	90 - 100%	(2)-8	No information available	540-84-1

Pollutant Release and Transfer Registry (PRTR)

Not applicable.

Industrial Safety and Health Law

ISHL Notifiable Substances - information (safety data sheet) to be supplied; Industrial Safety and Health Law enforcement order Table 9 (related to Industrial Safety and Health Law article 57-2 and ISHL Ordinance Article 34-2-4)

Chemical name	ISHL Notifiable Substances	Threshold Values (%)
Isooctane 540-84-1	ISHL Notifiable Substances	1

Poisonous and Deleterious Substances Control Law Not applicable

4. FIRST AID MEASURES

First aid measures

General advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Inhalation	Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed pulmonary edema may occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.
Ingestion	Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Aspiration hazard if swallowed - can enter lungs and cause damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical advice/attention.
Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing.
Note to physicians	Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

5. FIRE-FIGHTING MEASURES

Flammable Properties	HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Containers may explode when heated. Many liquids are lighter than water.
Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special Extinguishing Media	Cool drums with water spray.
Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.
Other Information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.
Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.
Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.
Reference to other sections	See section 8 for more information. See section 13 for more information.

7. HANDLING AND STORAGE

Handling

Advice on safe handling	Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.
--------------------------------	---

Storage

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.
---------------------------	--

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure guidelines

Chemical name	Japan	ISHL Working Environmental Evaluation Standards - Administrative Control Levels	ACGIH TLV
Isooctane 540-84-1	-	-	TWA: 300 ppm

Biological occupational exposure limits Not applicable

Engineering controls Showers
Eyewash stations
Ventilation systems.

Personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Hand protection Wear suitable gloves. Impervious gloves.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Environmental exposure controls No information available.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state Liquid
Appearance Clear
Odor Petroleum
Color No information available
Odor Threshold No information available

Property	Values	Remarks Method
pH	No data available	
Melting / freezing point	No data available	None known
Boiling point / boiling range	96°C °C	
Flash Point	-5°C C	
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known

Relative density	0.720	
Water Solubility	Insoluble	
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	398°C	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Viscosity	No data available	None known
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening Point	No information available
Molecular Weight	No information available
VOC Content (%)	~93%
Liquid Density	No information available
Bulk Density	No information available
Particle Size	No information available
Particle Size Distribution	No information available

10. STABILITY AND REACTIVITY

Reactivity	No information available.
Stability	Stable under normal conditions.
Explosion Data	
Sensitivity to Mechanical Impact	None
Sensitivity to Static Discharge	Yes
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong acids. Strong bases. Strong oxidizing agents.
Hazardous Decomposition Products	None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity**Product Information**

Inhalation	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Specific test data for the substance or mixture is not available. Irritating to eyes. (based on components).
Skin contact	Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-dust/mist) 11.85 mg/L

Unknown acute toxicity

100 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

100 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Numerical measures of toxicity - Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Isooctane 540-84-1	> 2500 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 47.4 mg/L (Rat) 1 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity No information available.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure No information available.

Target Organ Effects Respiratory system. Eyes. Skin.

Aspiration hazard May be fatal if swallowed and enters airways.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Persistence and Degradability No information available.

Mobility in soil No information available.

Mobility No information available.

Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

14. TRANSPORT INFORMATION

IMDG/IMO

UN-No.	UN1262
Proper Shipping Name	OCTANES
Hazard Class	3
Packing Group	II
EmS-No.	F-E, S-E
Marine Pollutant	This product contains a chemical which is listed as a marine pollutant according to IMDG/IMO
Description	UN1262, OCTANES (ISOOCTANE), 3, II, (-7°C C.C.), MARINE POLLUTANT

ADR

UN-No.	UN1262
Proper Shipping Name	OCTANES
Description	UN1262, OCTANES, 3, II, ENVIRONMENTALLY HAZARDOUS
Hazard Class	3
Packing Group	II
Environmental hazard	Yes
Classification code	F1
Tunnel restriction code	(D/E)

IATA

UN-No.	UN1262
Proper Shipping Name	OCTANES
Hazard Class	3
Packing Group	II
ERG Code	3H
Description	UN1262, OCTANES, 3, II

Japan

UN Number	UN1262
Proper Shipping Name	OCTANES
Hazard Class	3
Packing group	II
Special Provisions	UN1262, OCTANES (ISOOCTANE), 3, II, (-7°C C.C.), MARINE POLLUTANT

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations

Japan

Pollutant Release and Transfer Registry (PRTR)

Not applicable

Industrial Safety and Health Law

Dangerous Substances

Industrial Safety and Health Law enforcement order Table 1 (related to article 6 and article 9-3)

Flammable substance

Harmful Substances Whose Names Are to be Indicated on the Label

Harmful Substances - names to be indicated on the label; Industrial Safety and Health Law enforcement order Table 9 (related to Industrial Safety and Health Law article 57 and ISHL Ordinance Article 33)

ISHL Notifiable Substances

ISHL Notifiable Substances - information (safety data sheet) to be supplied; Industrial Safety and Health Law enforcement order Table 9 (related to Industrial Safety and Health Law article 57-2 and ISHL Ordinance Article 34-2-4)

Fire Service Law:

Verify that requirements related to using, handling, and storing substances subject to prohibition, authorization or restriction are met

Chemical name	Fire service law group	Hazardous material	Hazard rank
Isooctane 540-84-1	4	Flammable liquids	II

Act on the Evaluation of Chemical Substances and Regulation of Their Manufacture, etc. (CSCL)

Not applicable

Marine Pollution Prevention Act

Marine pollutant in accordance with the Law Regarding the Prevention of Marine Pollution and Maritime Disaster and its Ordinance, and the Standards for the Carriage of Dangerous Goods in Ships, Table 1

Air Pollution Control Law

Air pollutants with regulated emissions standards, Air Pollution Control Act article 3

International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Export Notification requirements Not applicable

International Inventories

TSCA	Contact supplier for inventory compliance status.
DSL/NDSL	Contact supplier for inventory compliance status.
EINECS/ELINCS	Contact supplier for inventory compliance status.
ENCS	Contact supplier for inventory compliance status.
KECL	Contact supplier for inventory compliance status.
PICCS	Contact supplier for inventory compliance status.
AICS	Contact supplier for inventory compliance status.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

16. OTHER INFORMATION

Prepared By Product Stewardship
 23 British American Blvd.
 Latham, NY 12110
 1-800-572-6501

Issuing Date 15-Sep-2016

Revision Date 13-Apr-2017

Revision Note No information available

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	-	Skin designation
C	Carcinogen		

Disclaimer

This SDS complies with the requirements of JIS Z 7250:2010 and JIS Z 7252:2009 (Japan). The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

End of Safety Data Sheet